

# Easy Line Remote Control

## Technical data

Dimensions (L x W x H)	84 x 32 x 11.5 mm (3.3 x 1.3 x 0.5")
Weight	26.4 g (9.3 oz), battery included
Color	Grey
Operating conditions	0° to +45° Celsius (32° to 113° Fahrenheit)
Transport and storage conditions	-20° to +60° Celsius (-4° to +140° Fahrenheit)
Humidity during storage	0% to 70% (non condensing)
Humidity during operation	0% to 95% (non condensing)
Included parts	Lanyard, CR 2032 battery
Ingress protection	IP52



## Power supply

Battery	CR 2032
Operating time	12 month average use

## Radio information

Antenna type	Monopole antenna
Operation frequency	2.4 GHz – 2.48 GHz
Modulation	GFSK
Radiated power	< 2.8mW

# Standards applied

Emissions standards	EN 60601-1-2:2015
	IEC 60601-1-2:2014
	EN 55011:2009+A1
	CISPR11:2009/AMD1:2010
	CISPR22:1997
	CISPR32:2012
	ISO 7637-2:2011
	CISPR25:2016
	EN 55025:2017
Immunity standards	EN 60601-1-2:2015
	IEC 60601-1-2:2014
	EN 61000-4-2:2009
	IEC 61000-4-2:2008
	EN 61000-4-3:2006+A1+A2
	IEC 61000-4-3:2006+A1+A2
	EN 61000-4-4:2012
	IEC 61000-4-4:2012
	EN 61000-4-5:2014
	IEC 61000-4-5:2014
	EN 61000-4-6:2014
	IEC 61000-4-6:2013
	EN 61000-4-8:2010
	IEC 61000-4-8:2009
	EN 61000-4-11:2004
IEC 61000-4-11:2004	
IEC 60601-1 (§ 4.10.2):2005	
ISO 7637-2:2011	
Legal manufacturer	Sonova AG
	Laubisrütistrasse 28
	CH-8712 Stäfa
	Switzerland



Sonova AG  
Laubisrütistrasse 28  
CH-8712 Stäfa, Switzerland



And importer for European Union:  
Sonova Deutschland GmbH  
Max-Eyth-Str. 20  
70736 Fellbach-Oeffingen, Germany

